## DC axial fans

□ 70 x 15 mm



Material: Housing: GRP<sup>1)</sup> (PBT)
 Impeller: GRP<sup>1)</sup> (PA)

Direction of air flow: Exhaust over strutsDirection of rotation: Counterclockwise,

looking towards rotor Via single wires AWG 24 to

 $\begin{array}{c} \text{AWG 28, TR 64} \\ \text{Weight:} \end{array}$  53 g

Possible special versions:
 (See chapter DC fans - specials)

- Speed signal
- Go / NoGo alarm
- Moisture protection


1) Fiberglass-reinforced plastic

**Connection:** 

Series 700 F  Nominal data	Air flow	Air flow	Nominal voltage	Voltage range	Sound pressure level	Sound power level	Sintec sleeve bearings Ball bearings	Power consumption	Nominal speed	Temperature range	Service life L <sub>10</sub> (40 °C) ebm-papst standard Service life L <sub>10</sub> (T <sub>max</sub> ) ebm-papst standard	Life expectancy L <sub>10IPC</sub> (40 °C) see page 17	Curve
Туре	m³/h	cfm	VDC	VDC	dB(A)	Bel(A)	■/■	Watts	rpm <sup>-1</sup>	°C	Hours	Hours	
712 F/2L-005*	28	16.5	12	813.8	25	4.7		0.6	3 300	-20+70	60 000 / 30 000	102 500	1
712 F/2M-006*	36	21.2	12	813.8	32	5.0		1.1	4 300	-20+70	60 000 / 30 000	102 500	2
712 F	44	25.9	12	813.8	38	5.3		1.7	5 300	-20+70	60 000 / 30 000	102 500	3
714 F	44	25.9	24	1828	38	5.3		1.5	5 300	-20+70	60 000 / 30 000	102 500	3
Subject to change													

\*Version with 3-pin

Molex plug housing Molex Contacts 22-01-2035 08-50-0113




Air performance measured according to: ISO 5801. Installation category A, without contact protection. Noise: Total sound power level  $L_{I\!\!M}A$  ISO 103002 measured on a hemisphere with a radius of 2 m. Sound pressure level  $L_{I\!\!P}A$  measured at 1 m distance from

fan axis.

The values given are applicable only under the specified measuring conditions and may differ depending on the installation conditions.





2016-01